No. 1935/Purchase Office/CMDR/CMDR Equipments/2014

Telephone : 91-532-227+1122, 1123 Fax : 0532-2545341, 2545822

GRAM : MNNIT

Website : http:\\www.mnnit.ac.in
Email : spo@mnnit.ac.in.

: spo@mnnit.ac.in, fip@mnnit.ac.in



elschyly ug: jRVh, ils lexdh l lillu bylgleln

Dated: 03/12/2014

इलाहाबाद—211004 (भारत)

Motilal Nehru National Institute of Technology Allahabad

Allahabad-211004 (India)

An Institute of National Importance as Declared by NIT Act, GOI, 2007

INVITATION FOR SUPPLY OF SONICATOR, THERMAL CYCLER, LYOPHILIZER, HYBRIDIZATION OVEN, WATER PURIFICATION SYSTEM, ULTRASONIC BATH

(For Contracts value estimated to cost less than Rs.25lakhs)

1	Closing Date/Time for submission of Quotations	30/12/2014; 16:30 Hrs.
1	Opening Date/Time of Quotations	,
	·	30/12/2014; 17:00 Hrs.
3	Quotations to be submitted at	The Office of Faculty-In-charge (Purchase)
		M.N.N.I.T. Allahabad, Allahabad-211 004 (U.P.)
4	Place of opening of quotations	The Office of Faculty-In-charge (Purchase)
		M.N.N.I.T. Allahabad, Allahabad-211 004 (U.P.)
5	Tender Fee	Rs. 200.00 (Non-refundable), in form of a Demand
		Draft drawn in favor of DIRECTOR, MNNIT
		Allahabad.
6	Earnest Money Deposit (EMD)	Rs. 52,500/- (Rs. In words Fifty two thousand five
		hundred only), in form of FDR /Bank guarantee,
		from any of the Commercial Banks, drawn in
		favour of "Director, MNNIT Allahabad" payable at
		Allahabad, and valid for a period of 45 days
		beyond the final bid validity period

Τo,

Dear Sir

You are invited to submit your most competitive quotation for the following goods/equipments. The quotation should be sent directly to the undersigned under Sealed Cover marked "Quotation Reference No., Date", and "The Due Date:

SI. No.	Brief Description of the Goods	Quantity.	Place Of Delivery	Installation Requirement
1.	Sonicator	01 No.	M. N. N. I.T.	Yes
2.	Thermal Cycler	01 No.	Allahabad	
3.	Lyophilizer	01 No.		
4.	Hybridization Oven	01 No.		
5.	Water Purification System	01 No.		
6.	Ultrasonic Bath	01 No.		
	(Detailed specifications attached at Annexure-B)			

The sealed tenders must be submitted in the Office of the Faculty In-charge (Purchase), on or before **due date & time** as **mentioned above** in the office of the undersigned, in the presence of bidder's authorized representatives, who choose to attend and shall sign a register evidencing their attendance.

The tender/quotations NOT submitted in the prescribed format or Incomplete in any respect will be outrightly rejected.

Faculty in-Charge, Purchase MNNIT Allahabad

GENERAL TERMS & CONDITION (GCC)

1. Bid Price

- (a) The contract shall be for the full quantity as described above. Corrections, if any, shall be made by crossing out, initialing, dating and rewriting.
- (b) All duties, taxes and other levies payable by the contractor under the contract shall be included in the total price.
- (c) The rates quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
- (d) The prices should be quoted in Indian Rupees only for indigenous items. For imported items/Equipments, the prices should be quoted in foreign currency.
- (e) Each bidder shall submit only one quotation.

2. Validity of Quotation

Quotation shall remain valid for a period not less than 90 days after the deadline date specified for submission.

3. Evaluation of Quotations

- (a) The purchaser will evaluate and compare the quotations determined to be substantially responsive, i.e., which
 - (i) are properly signed; and
 - (ii) conform to the terms and conditions, and specifications.
 - (iii) will be with tender fees, and EMD required, if any.
- (b) The Quotations would be evaluated separately for each item.

4. Award of Contract

The Purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price.

- Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.
- The bidder whose bid is accepted will be notified for the award of contract by the Purchaser prior to expiration of the quotation validity period. The terms of the accepted offer shall be incorporated in the purchase order if falls under Govt. purchase rules, i.e., GFR-2005

5. Formats and Signing of Bid

- Each & every pages of the submitted bid must carry the page numbers.
- The bidders are not allowed to make additional and alteration in the tender document, any additions and alteration in the tender document, any additions and alterations shall be at bidder's risk. Conditional/modified tender are liable to be rejected.
- The tender/quotations NOT submitted in the prescribed format or Incomplete in any respect will be outrightly rejected.
- If the bid submitted without compliance sheet details of equipments the bid will be outrightly rejected.
- The bid shall be typed or written in indelible ink and shall be signed by the Bidder/Tenderer or a person or persons duly authorized to bind the Bidder/Tenderer to the Contract. All pages of the bid, except for unamended printed literature, shall be initialed by the person or persons signing the bid.
- Any interlineations, erasure or overwriting shall be valid only if they are initiated by the persons or persons signing the bid.
- The Bidder shall furnish information as described in the Form of Bid on commissions or gratuities, if any, paid or
 to be paid to agents relating to this Bid, and to contract execution if the Bidder is awarded the contract.
- Payment condition: 100% Payment shall be made only after satisfactory delivery and installation of the goods.
 Advance payment is not permitted.
- 7. Normal Commercial warranty/ guarantee shall be applicable to the supplied goods.
- 8. Payment will be cleared through e-payment mode (Format of e-payment form given at Annexure-D)

INSTRUCTIONS/GUIDELINES TO BIDDERS (ITB)

- 1. Bidders who had supplied the Government departments, PSUs/NITs/IITs and reputed Institutions and Organizations should only apply.
- 2. The bidder should enclose the cliental list with contact address along with Phone/Fax for reference, for the quoted item.
- 3. Please quote the prices of F.O.R. Motilal Nehru National Institute of Technology Allahabad, Allahabad.
- 4. The Bidders are requested to submit their Quotation with EMD in the form of Demand Draft/ Bank Guarantee/ Short term Deposit of the cost of equipments/items in favor of "The Director, MNNIT, Allahabad" payable at Allahabad. Quotation without EMD will be summarily rejected. EMD's of all Bidders will be returned back after the purchase order /contract agreement is issued to successful bidder.
- 5. Successful Bidders must have to submit the performance security @ 10% of the purchase order or contract value and it will be retained up to the warranty period.
- 6. The bidder should enclose relevant documents wherever necessary to substantiate his eligibility.
- 7. The Institute is eligible for and can provide necessary documentation for Custom/Excise and Octroi exemption on demand, if permitted under rule.
- 8. Motilal Nehru National Institute of Technology Allahabad, Allahabad, reserves the right to reject, accept any or whole or part of any of the tender without assigning any reason thereof and no claim will be heard. In case of dispute, the decision of The Director, MNNIT, and Allahabad will be final and binding.
- 9. If the successful bidder is not able to supply the goods items within the delivery date specified in the purchase order, the purchase order will be automatically treated as cancelled after expiry of delivery date period. The vendor will have to submit an undertaking in this regard that this condition is acceptable to him. In case of extra ordinary circumstances the vendors must send a request for extension of validity of purchase orders, with proper justification prior to the expiry of validity date for consideration.
- 10. In case of sophisticated equipments, an on-site training needs to be provided with no extra cost.
- 11. The quotation must be accompanied by leaflets/operation manuals/books etc.
- 12. Wherever applicable the vendors must quote the branded /desired items.

CHECK LIST (ON THE LETTER HEAD OF THE BIDDER)

The Bid will be the compilation of following documents, along with required supporting documents. No document in support of minimum eligibility criteria will be accepted / entertained after opening of tender.

SI. No	Documents
1.	Cover letter by bidder (On the Letter Head of the Bidder)
2.	Tender Fee
3.	Earnest Money Deposit (EMD), if required
4.	Cliental List for quoted item
5.	Annexure-A: Bid Proposal Sheet (On the Letter Head of the Bidder)
6.	Annexure-B: Compliance of bidder with reference to various equipments (On the Letter Head of the Bidder)
7.	Annexure-C : PRICE BID (On the Letter Head of the Bidder)
8.	Annexure-D: PROFORMA FOR DIRECT PAYMENT/TRANSFER TO BANK ACCOUNT BY MNNIT ALLAHABAD

ANNEXURE-A

BID PROPOSAL SHEET (ON THE LETTER HEAD OF THE BIDDER)

To

Faculty In-charge (Purchase)
MNNIT Allahabad, Allahabad

Subject: Supply and Installation of "Sonicator, Thermal Cycler, Lyophilizer, Hybridization Oven, Water Purification System, Ultrasonic Bath" at MNNIT Allahabad, Allahabad.

Dear Sir,

We, the undersigned Tenderers, having read and examined in detail the specifications as specified in this document in respect of Supply and Installation of Sonicator, Thermal Cycler, Lyophilizer, Hybridization Oven, Water Purification System, Ultrasonic Bath at MNNIT Allahabad, Allahabad do hereby propose to supply the required products and services.

Tender No.						
Tender Fe	es submitted	YES / NO	(Please strike off whatever is not applicable)			
Amount	Mode	Date of Issue	Name of Bank	Valid up to		
	Demand Draft					
EMD submitted		YES / NO	NO (Please strike off whatever is n			
Amount	Mode	Date of Issue	Name of Bank	Valid up to		
	Demand Draft					

- (i) ADDITIONAL PURCHASE/WORK ORDER: We understand that the MNNIT Allahabad, Allahabad, in case of the requirements may also place repeat purchase order/work order on the company. In such cases, we shall accept and execute all the purchase/work order placed on us by MNNIT Allahabad, Allahabad.
- (ii) **BID PRICING:** We further declare that the prices stated in our proposal are in accordance with your Terms & Conditions in the bidding document. We further understand that the quantities as specified in this Tender may increase or decrease at the time of Award of Purchase Order as per the requirements of MNNIT Allahabad, Allahabad.
- (iii) **QUALIFYING DATA:** We confirm that we satisfy the qualifying criteria and have attached the requisite documents as documentary proofs. In case you require any further information/documentary proof in this regard during evaluation of our bid, we agree to furnish the same in time to your satisfaction.
- (iv) CONTRACT PERFORMANCE SECURITY: We hereby declare that in case the contract is awarded to us, we shall submit the performance Guarantee Bond in the form of Bank Guarantee for the amount mentioned at clause No. 5 in ITB of the total order value.
- (v) PAYMENT TERMS: We hereby declare that in case the contract is awarded to us, we agree with payment terms specified in the tender documents.
- (vi) CERTIFICATE AND DECLARATION:
 - a) I/We certify that no addition/modification/alteration has been made in the Original Tender Document. If at any stage addition /modification /alteration is noticed in the Original Document, I/We will abide by the terms and conditions contained in the original tender document, failing which MNNIT Allahabad reserves the right to reject the tender and/or cancel the contract
 - b) It has been certified that all information provided in tender form is true and correct to the best of my knowledge and belief. We hereby declare that our proposal is made in good faith, without collusion or fraud. No forged /tampered document(s) are produced with tender form for gaining unlawful advantage. We understand that MNNIT Allahabad is authorized to make enquiry to establish the facts claimed and obtained confidential reports from clients.
 - c) In case it is established that any information provided by us is false / misleading or in the circumstances where it is found that we have made any wrong claims. Further MNNIT Allahabad is also authorized to blacklist our firm/company/agency and debar us in participating in any tender/bid in future.
 - d) I / We assure the Institute that neither I /We, nor any of my /our workers, will do any act which is improper / illegal during the execution in case the tender is awarded to us.
 - e) I / We assure the Institute that I / We will NOT be outsourcing any work specified in the tender document, to any other firm.
 - f) Neither I / We, nor anybody on my /our behalf will indulge in any corrupt activities /practices in my /our dealing with the Institute.
 - g) Our Firm / Company / Agency is not been blacklisted or banned by any Govt. Department, PSU, University, Autonomous Institute or any other Govt. Organization.
 - h) I/We certify that, I have understood all the terms & conditions (GCC and ITB etc.), as indicated in enquiry of the tender document, and hereby accept all the same completely.
 - i) I/We, further certify that I/We, possess all the statutory /non-statutory registrations, permissions, approvals, etc., from the Competent Authority for providing the requisite services,
 - j) We understand that you are not bound to accept the lowest or any bid you may receive.
 - k) I/We hereby declare that this tender on acceptance communicated by you shall constitute a valid and binding contract between us.
 - I) I/We certify that the submitted quotation is duly paginated and contains from page no. 1 to

Signature and Seal of the Manufacturer/Bidder

Technical Compliance of Goods (ON THE LETTER HEAD OF THE BIDDER)

SONICATOR 1. Cell High Intensity Ultra Sonic Liquid Processor 250 microliters to 100 mm. 2. Ultrasonic power should be maximum 750. 3. 20 kHz, automatic tuning, energy (joules) monitor, digital wattmeter. 4. Integrated temperature controller, microprocessor - based, programmable. 5. LCD screen with user prompts, sealed converter, alpha- numeric display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 see to 10 hour process timer, 7. 1 see to 10 hour process timer, 8. Automatic variable amplitude control. 9. Automatic Variable amplitude control. 10. Oranicatic uning and frequency control. 9. Automatic Variable amplitude control. 11. Disconnect converter cable, instruction manual. Tool Kil. 12. Supplied with Laboratory jack and noise abatting material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. "probe whold pea bactodavable: 14. Provision for following probe volume 15. "probe whold pea bactodavable: 14. Provision for following probe volume 16. "Si probe for 250ul-10ml. 17. High gain probe lacifly 100% amplitude facility. 18. Stabilizer 19" 19. Sandard Warranty 2. THERMAL. 2. THERMAL. 2. Whould a system Block option should be 48v48v2.ml, or 32x3v0.2ml or 96 well with gradient facility, capable to run 2 or 3 program or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature accuracy 30.2 degree centigrade will to well within 10sec centrigrade 5. Temperature accuracy 30.2 degree centigrade will to well within 10sec centrigrade 6. Gradient accuracy 30.2 degree centigrade will to well within 10sec centrigrade. 9. Memory 2 1000 typical programs orhozard block 10. Programming options Semi-Carphalic, Let — based automatic 11. P.C. compatibility Muse, USB flash Drive bar code reader. 12. Color Display screen 13. Reportable run logs, system error logs 14. With 2KVA (UPS) 15. Sandard Warranty 16. Congatibility windows XP or higher, USB peripheral compatibility Muse, USB flash Drive ba	SI. No.	Descriptions/Specification	Quantity	Compliance (Yes/No)	Quoted Model
100mm. 2. Utrasonic power should be maximum 750. 3. 20 kHz, automatic tuning, energy (joules) monitor, digital wattmeter. 4. Integrated temperature controller, interoprocessor - based, programmable. 5. LCD screen with user prompts, sealed converter, alpha—numeric display. 6. Upto 10 procedures to facilistae protocol duplication. 7. 1 sec to 10 hour process immar. 7. 1 sec to 10 hour process immar. 8. 1 sec to 10 hour process immar. 8. 1 sec to 10 hour process immar. 9. 1 sec to 10 hour process immar.		SONICATOR	01 No.	(100,110)	ouo.
100mm. 2. Utrasonic power should be maximum 750. 3. 20 kHz, automatic tuning, energy (joules) monitor, digital wattmeter. 4. Integrated temperature controller, interoprocessor - based, programmable. 5. LCD screen with user prompts, sealed converter, alpha—numeric display. 6. Upto 10 procedures to facilistae protocol duplication. 7. 1 sec to 10 hour process immar. 7. 1 sec to 10 hour process immar. 8. 1 sec to 10 hour process immar. 8. 1 sec to 10 hour process immar. 9. 1 sec to 10 hour process immar.					
3. 20 kHz, automatic tuning, energy (joules) monitor, digital wattmeter. 4. Integrated temperature controller, microprocessor - based, programmable. 5. LCD screen with user prompts, sealed converter, alpha—numeric display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 sec to 10 hour process timer, 8. Automatic Variable amplitude control. 9. Automatic Variable amplitude control. 10. Independently controllable from 0.1 second to 59 seconds, overload programmable. 11. Exploited with Laboratory jack and noise abating material with Support rod and converter Caller, lest uction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Caller. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. 's' probe of the Teplaceable tip and for volume 10ml to 250ml. 16. 1/3" probe for 250u1-10ml. 17. High pain probe facility 100% amplitude facility. 18. Stabilizer 19th 19th 19th 19th 19th 19th 19th 19th					
4. Integrated temperature controller, microprocessor - based, programmable. 5. LCD screen with user prompts, sealed converter, alpha- numeric display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 sec to 10 hour process timer, 8. Automatic uning and frequency control. 9. Automatic Variable amplitude control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection criciu with mortif cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with protection criciu with mortif cycle. 13. Protos should be autoclavable. 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 18." grobe for 250u-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stablazer 19" 19. Standard Warranty 2. THERMAL CYCLER 11. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x480.2 ml, or 32x3x0.2 ml or 58 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-9 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed temperature and forws 7. Temperature Uniformity ±x0.5 degree centigrade will to well within 10sec of arrival at 80 degree centigrade. 8. Memory ≥ 1000 typical programs onboard. 9. Temperature complexity of the degree or better centigrade will be seen to see the second or seeder. 10. Condense temperature. SoCC 11. Little Benchitop Freeze Dry System with Teffon-Coated Collector 12. Color Display screen 13. Kandard Warranty 14. With 2K/A (UPS) 15. Standard Warranty 16. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Saf		·			
programmable. 5. LCD screen with user prompts, sealed converter, alpha- numeric display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 sec to 10 hour process timer. 8. Automatic Uning and frequency control. 9. Automatic Variable amplitude control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with no/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for foliowing probe volume 10ml to 250ml. 16. 18 probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Sabibar 19 19. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously. 19. Mobility system gradient facility and for support of programmating and simultaneously. 19. Mobility system gradient or user defined gradient. 19. Maymum maniprig task 4-6 degree centigrade. 10. Temperature range should be 49 degree of better centigrade. 10. Temperature at end rows. 10. Temperature at end rows. 11. Temperature at 30 degree contigrade well to well within 10sec of arrival at 90 degree contigrade well to well within 10sec of arrival at 90 degree contigrade. 10. Temperature at end rows. 11. Temperature control modes Calculated and block. 12. Temperature undersone Semi-Graphical, text — based automatic. 13. Properature is depressed by the service of the ser					
5. LCD screen with user prompts, sealed converter, alpha-numeric display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 ase to 10 hour process timer, 8. Automatic tuning and frequency control. 9. Automatic tuning and frequency control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with on/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. "F' probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizar 19" 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 1. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 deprece entigrade 4. Temperature range should be 4-99 degree or better centigrade 4. Temperature are gradient descripted of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature uncertool modes Calculated and block 10. Programming options Semi-Graphical, lext – based automatic 11. PC compability windows XP or higher, USB peripheral compability windows XP or h		· · · · · · · · · · · · · · · · · · ·			
display. 6. Upto 10 procedures to facilitate protocol duplication. 7. 1 sec to 10 hour process timer, 8. Automatic Variable amplitude control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with on/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable ity and for volume 10ml to 250ml. 16. ½" probe of 100 probe facility 100% amplitude facility. 18. Stabizar 19" 19. Standard Warranty 2. **THERMAR CYCLER** 11. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. **Marka Cycler** 16. Thermal Cycler with gradient or user defined gradient. 27. **Marka Cycler** 18. Standard Warranty 28. **Marka Cycler** 19. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 98 well with gradient or user defined gradient. 29. **Marka Cycler** 10. **Marka Cycler** 10. **Marka Cycler** 11. Thermal Cycler with gradient or user defined gradient. 29. **Marka Cycler** 10. **Marka Cycler** 10. **Marka Cycler** 11. Thermal Cycler** 12. **Marka Cycler** 13. **Marka Cycler** 14. **Marka Cycler** 15. **Temperature acoursey 40.2 degree centigrade 16. **Gradient accuracy 40.2 degree centigrade 17. **Temperature action of the degree centigrade will to well within 10sec of arrival at 90 degree centigrade of programmed temperature at end rows 18. **Marka Cycler** 19. **Temperature action of the degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well within 10sec of arrival at 90 degree centigrade will be well will be well will be					
6. Uplo 10 procedures to facilitate protocol duplication. 7. 1 sec to 10 hour process timer. 8. Automatic tuning and frequency control. 9. Automatic tuning and frequency control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with on/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizer 19" 19. Standard Warranty 2. THERMAL CYCLER 2. Intermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 4. Temperature are success of temperature and temperature at end rows 7. Temperature and temperature and temperature at end rows 8. Memory 2-1000 typical programs onboard 9. Temperature undermity <-0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade of programmed temperature at end rows 9. Temperature undermity <-0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 19. Temperature undermity <-0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 19. Temperature undermity <-0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 19. Temperature undermity <-0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 20. Temperature control modes Calculated and block 21. Programming options Sem-Gragifical, text — based automatic 22. Color Display screen 23. Reporting experiments the text of the programming options Sem-Gragifical, text — based a					
8. Automatic turning and frequency control. 9. Automatic turning is amplitude control. 10. Independently controllable implitude control. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½* Probe with replaceable itip and for volume 10ml to 250ml. 16. 1/8* probe for 250u-1-0ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizer 19* 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 98 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature rampe should be 49x48x0.2 ml, or 32x3x0.2ml or 98 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature are are 90.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard temperature are are 91 degree centigrade. 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows ½F or higher. USB peripheral compatibility Mouse, USB flash Drive bar code reader. 2. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With 2XVA (UPS) 15. Standard Warranty 15. Standard Warranty 16. Liter Benchtop Freeza Dry System with Tellon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -550C 4. Condenser temperature: -550C 5. Compatible rotary vaccuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back					
9. Automatic Variable amplitude control. 10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with on/off cycle. 11. Disconnect convorter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Claup. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250u-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizer 19" 19. Standard Warranty 2. THERMAL CYCLER 10. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 49x9 degree or better centigrade 5. Temperature ange should be 499 degree or better centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade well to well within 10sec of arrival at 90 degree centigrade with sepreparture and rows 7. Temperature unformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text — based automatic 11. PC compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 16. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 2. Condenser temperature: -550C 3. Condenser temperature: -550C 4. Condenser temperature: -550C 5. Compatible rotary vacuum pump, 230 Volts, designed for use with acqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 4. Hyperiolization over adjustable be					
10. Independently controllable from 0.1 second to 59 seconds, overload protection circuit with on/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½* Probe with replaceable it pain dor volume 10ml to 250ml. 16. 1/8* probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizer 19th. 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously. 2. Modular system Block option should be 48x48y0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 5. Temperature range should be 49x49 degree or better centigrade 5. Temperature and should be 49x49 degree or better centigrade 6. Gradient accuracy a0.2 degree centigrade of programmed temperature at end rows 7. Temperature and 180 degree centigrade well to well within 10soc of arrival at 90 degree centigrade and block 10. Programming options Semi-Graphical, text — based automatic 11. Pc compatibility Mouse, USB flash Drive bar coole reader. 12. Color Display screen 13. Reporting : exportable run logs : system error logs 14. With 2kVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 10. Inter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -550C 4. Condenser temperature: -550C 5. Condenser temperature: -550C 6. Condenser temperature: -550C 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCPC/CF C-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration and of the parameters. 11. Standard Warranty 12. Temp. range: Amb.					
protection circuit with on/off cycle. 11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250u-10ml. 17. High gain probe facility 100% amplitude facility. 18. Sabitaer 19" 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature at gradient facility, expanded to programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature bulnformity temperature at end rows 7. Temperature option grade 4-6 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory 2 1000 Upical programs onboard 9. Temperature ontrol modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibi		·			
11. Disconnect converter cable, instruction manual. Tool Kit. 12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabizer 19" 19. Standard Warranty 2. THERMAL CYCLER 1 Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48v0.2ml, or 32x3v0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature ange should be 4-99 degree or better centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature outriof modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral					
12. Supplied with Laboratory jack and noise abating material with Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. ½" probe for 250u-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabitzer 19th. 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature range should be 4-99 degree or better centigrade 6. Gradient accuracy 40.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature bindrimity < https://doi.org/10.1007/stal/programs on you will within 10sec of arrival at 90 degree centigrade. 8. Memory 2 1000 Upical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility windows XP or bigher, USB peripheral c		· ·			
Support rod and converter Clamp. 13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 1/8" probe for 250ul-10ml. 17. Hgfh gain probe facility 100% amplitude facility. 18. Stabilizer 19 ¹⁰ 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature range should be 4-99 degree or better centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Misouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1 Litter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -550C 4. Condenser capacity: rimi. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCPC/CFC-tree refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standa					
13. Probe should be autoclavable: 14. Provision for following probe volume 15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 18³ probe for 250±1-0ml. 17. High gain probe facility 100% amplitude facility. 18. Stablizer 10³ 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity x±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. Pc compatibility indiows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. Writh 2KVA (UPS) 15. Standard Warranty 16. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltagie: 230 Volts / 50Hz 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltagie: 230 Volts / 50Hz 3. Condenser temperature: -550C 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-tree refrigeration or/off, Vacuum on/off 11. Standard Warranty 12. Temp, range: Amb					
15. ½" probe with replaceable tip and for volume 10ml to 250ml. 16. 18" probe for 250ul-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stabilizer 19" 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity x±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility indrows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. Writh zKVA (UPS) 15. Standard Warranty 16. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser capacity: rinin. 2 lit. 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-tree refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 12. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 4. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 4. Temp, variation: ±0.5 °C		13. Probe should be autoclavable:			
16. 1/8" probe for 250u1-10ml. 17. High gain probe facility 100% amplitude facility. 18. Stablizer 19 th 19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously. 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4.99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity ≥0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility windows XP or higher, USB periph					
17. High gain probe facility 100% amplitude facility. 18. Stabizer 19 ¹⁹ 19. Standard Warranty 2. THERMA CYCLER 1. THERMA CYCLER 1. THERMA CYCLER 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity <40.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral condereder. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration to LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on					
19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity ≤0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral conditions and the peripheral compatibility windows XP or higher, USB peripheral conditions and the peripheral compatibility windows XP or higher, USB peripheral conditions and the peripheral compatibility windows XP or higher, USB peripheral conditions and the peripheral compatibility windows XP or higher, USB peripheral conditions and the peripheral conditions and t					
19. Standard Warranty 2. THERMAL CYCLER 1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature ange should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity < ±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 11. Standard Warranty 12. Temp. range: Amb. Ambient to 80 °C 3. Temp. tange: Amb. Ambient to 80 °C 4. Temp. variation: ±0.5 °C 4. Temp. variation: ±0.5 °C		17. Tiigit gain probe taoiiity 100% ampiitude taoiiity. 18. Stablizer 19 th			
1. Thermal Cycler with gradient facility, capable to run 2 or 3 program simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature range should be 4-99 degree or better centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity ≤±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Litter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -550C 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CF-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration or/off, Vacuum on/off 11. Standard Warranty 12. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 4. Temp, variation: ±0.5 °C					
simultaneously 2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity ±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text → based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 17. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 12. Capacity: 20 Liters 2. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 3. Temp, range: Amb. Ambient to 80 °C 4. Temp. range: Amb. Ambient to 80 °C 4. Temp. range: Amb. Ambient to 80 °C 5. Temp. fluctuation (at 37 °C): ±0.1 °C	2.		01 No.		
2. Modular system Block option should be 48x48x0.2ml, or 32x3x0.2ml or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature bufformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. range: Amb. Ambient to 80 °C 4. Temp. variation: ±0.5 °C		1. Thermal Cycler with gradient facility, capable to run 2 or 3 program			
or 96 well with gradient or user defined gradient. 3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade well to well within 10sec of arrival at 90 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 (typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCPC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. range: Amb. Ambient to 80 °C 4. Temp. variation: ±0.5 °C					
3. Maximum ramping rate 4-6 degree centigrade 4. Temperature range should be 4-99 degree or beter centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility windows XP or higher, USB peripheral compatibility Midouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs; system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. range: Amb. Ambient to 80 °C 3. Temp. range: Amb. Ambient to 80 °C 4. Temp. variation: ±0.5 °C					
4. Temperature range should be 4-99 degree or better centigrade 5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser capacity : min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration LCD for display of set up and operating parameters. 11. Capacity : 20 Liters 2. Temp, range : Amb. Ambient to 80 °C 3. Temp fucutation (at 37 °C) : ±0.1 °C 4. Temp. variation : ±0.5 °C					
5. Temperature accuracy ±0.2 degree centigrade of programmed target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB llash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration LCD for display of set up and operating parameters. 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fucutation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
target at 90 degree centigrade 6. Gradient accuracy ±0.2 degree centigrade of programmed temperature at end rows 7. Temperature Uniformity <≥0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With ≥KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity : min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration LCD for display of set up and operating parameters. 11. Standard Warranty 4. HYBRIDIZATION OVEN 11. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
temperature at end rows 7. Temperature Uniformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text − based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With 2kVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 11. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity : min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
7. Temperature Uniformity <±0.5 degree centigrade well to well within 10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting : exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity : min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		6. Gradient accuracy ±0.2 degree centigrade of programmed			
10sec of arrival at 90 degree centigrade. 8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility Wouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CF-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
8. Memory ≥ 1000 typical programs onboard 9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs , system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
9. Temperature control modes Calculated and block 10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With ZKVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
10. Programming options Semi-Graphical, text – based automatic 11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
11. PC compatibility windows XP or higher, USB peripheral compatibility Mouse, USB flash Drive bar code reader. 12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
12. Color Display screen 13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		11. PC compatibility windows XP or higher, USB peripheral			
13. Reporting: exportable run logs, system error logs 14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
14. With 2KVA (UPS) 15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
15. Standard Warranty 3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
3. LYOPHILIZER 1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
1. Liter Benchtop Freeze Dry System with Teflon-Coated Collector 2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C	3.		01 No.		
2. Voltage: 230 Volts / 50Hz 3. Condenser temperature: -55oC 4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C	<u> </u>		- · · · · · · ·		
4. Condenser capacity: min. 2 lit 5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		2. Voltage: 230 Volts / 50Hz			
5. Microprocessor controlled operations with digital temp. and vacuum display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
display 6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
6. Drying chamber with shelves for bulk samples, plates, vials, bottles, etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
etc. 7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		, ,			
7. Compatible rotary vacuum pump, 230 Volts, designed for use with aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
aqueous samples with suitable filters and traps for oil mist and chemical vapors. Safety for oil suck back 8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
8. Suitable trolley or adjustable bench. 9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		aqueous samples with suitable filters and traps for oil mist and			
9. HCFC/CFC-free refrigeration LCD for display of set up and operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
operating parameters. 10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
10. Controls: Refrigeration on/off, Vacuum on/off 11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
11. Standard Warranty 4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
4. HYBRIDIZATION OVEN 1. Capacity: 20 Liters 2. Temp. range: Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C					
2. Temp. range : Amb. Ambient to 80 °C 3. Temp. fluctuation (at 37 °C) : ±0.1 °C 4. Temp. variation : ±0.5 °C	4.		01 No.		
3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		1. Capacity: 20 Liters			
3. Temp. fluctuation (at 37 °C): ±0.1 °C 4. Temp. variation: ±0.5 °C		2. Temp. range: Amb. Ambient to 80 °C			
·		3. Temp. fluctuation (at 37 °C) : ±0.1 °C			
5. Display type: LED		4. Temp. variation : ±0.5 °C			
		5. Display type : LED			

	6.	Display resolution : 0.5°C		
	7.	No. of rotisseries : 1		
	8.	Rotational speed range : 2 to 10 rpm		
	9.	Rocker speed range: 5 to 70 oscillation / minute		
	_	FEATURES:		
		Compact design		
	12.	Rotisserie and rocker in one unit		
	13.	Up and over door for accessibility		
	14.	Accurate temperature control		
	15.	Advanced safety features		
	16.	Variable speed control		
		Standard Warranty		
5.		FER PURIFICATION SYSTEM	01 No.	
	1.	Should contain pre treatment unit, a RO based water purification		
		system, ultra purification unit and purified water storage tanks.		
	2.	RO based water purification system included in the system should		
		be: Particle filtration, Spherical Activated Carbon, Catalyst, Dual		
		Reverse Osmosis Membranes, Optional Final Particle and Sterile		
		Filtration.		
	3.	The pre-treatment cartridge should consist with 20x50 mesh		
		activated carbon, a catalyst, and a 5µm depth filter to remove		
		oxidation agents, heavy metal ions, and particles from the feed		
		water at low temperature.		
	4.	System should consist of dual Pass 2 individual RO Membrane in		
	_	parallel operation (i.e. not in series).		
	5.	Display :Glass display with touch function should display parameter related to quality of water (conductivity of input and output water,		
		rejection rate monitor, Tank level ,temperature etc)		
	6.	There should be an option for 0.2 micron Sterile-grade filter for		
	0.	bacteria free filtrate		
	7.	24 hrs fully automatic system		
		Typical Resistivity : $< 0.05 \text{ M}\Omega$.cm at 25°C		
	9.	Bacteria : < 1 CFU/1000 ml		
	10.	Flow rate: upto 10 liter/hr at 25°C		
	11.	Particle ,Microorganism Retention: >99%		
	12.	Monovalent, Polyvalent ion Retention : upto 95%		
	13.	Recirculation of water in standby mode to maintain the purity of		
		water.		
		Should have facility for wall mounting		
	15.	Ultrapure water should be produced using Carbon –resin		
	40	technology with Resistivity up to 18.2MΩ x cm.		
		System should have Horizontally placed UV oxidation		
	17.	System should show 3 Water Dispensing Modes :		
	12	i) Manual ii) Time iii) Volume Controlled CE Certified		
		Additional cartridges and 0.22um filter may be provided.		
		Product Water Quality		
	-5.	Resistivity: 18.2 MΩ.cm		
		TOC: < 2 ppb		
		Particles: < 1/ml @ 0.2um		
		Bacteria: < 1 CFU/1000ml		
		Flow rate: Up to 2.0 I/min		
		Standard Warranty	04.11	
6.		TRASONIC BATH	01 No.	
	1. 2.	Volume: 10 Liters Frequency of Operation: Should operate in switchable double		
	۷.	Frequency of Operation: Should operate in switchable double frequencies at 30-35 KHz and 50-55 KHz.		
	3.	Amplitude Control: Amplitude or intensity is set through keyboard		
	J.	and can be varied from ~ 50% to 100% continuously, in step of 1%.		
		Output intensity of transducer should be set as per sample.		
	4.	LCD Display: Should have backlight LCD display which gives real		
		time information of set frequency, time, power, temperature of		
		water in the trough etc. Parameter should be selected from		
		displayed menu as per requirement.		
	5.	Digital Timer: Timing range from 1 minute to 2 Hours can be set		
		freely. Display should provide information for elapsed time and		
		ultrasonic ON/OFF time should be programmed.		
	6.	Heating Facility: Temperature should be set in the range of 20 °C		
		~ 60 °C. Display should provide real time display of set temperature		
		and actual temperature. The bath should provide ultrasonically		
	7	water temperature harmonization.		
	7.	Auto Alarm: The machine should alarm and power off when boiling dry.		
i	_	Standard Warranty		
	8.			

PRICE BID (ON THE LETTER HEAD OF THE BIDDER)

SI.	Brief Description of the Goods	Quantity	Quoted Unit Rate in Rs	Total Amount (in Rs.)		
No.		Quantity		In Figures	In Words	
1.	Sonicator	01 No.				
2.	Thermal Cycler	01 No.				
3.	Lyophilizer	01 No.				
4.	Hybridization Oven	01 No.				
5.	Water Purification System	01 No.				
6.	Ultrasonic Bath	01 No.				
	(Detailed specifications attached at Annexure-B)					

we agree to supply the above goods in accordance with the technical sp	pecifications for a total contract price
of within the period specified in the Invitation for Quotations.	
We also confirm that the normal commercial warrantee/guarantee of	months shall apply to the offered goods

Signature and Seal of the Manufacturer/Bidder

Note:

- 1. Preference will be given to ISO 9001-2000 certified manufacture/supplier, who can ensure the manufacturing of the machine as per the required testing standards/tender specifications within the specified tolerance limit.
- 2. Bidders should provide copies of original Memorandum and Articles of Association, defining the constitution of legal status, place of registration and place of business of the company.

ANNEXURE-D

PROFORMA FOR DIRECT PAYMENT/TRANSFER TO BANK ACCOUNT BY MNNIT ALLAHABAD

SI. No.	Particulars	Information
1.	Firm [Beneficiary] Name	
2.	Code No. allotted by the MNNIT Allahabad [If code is not allotted yet, please enclose a cancelled cheque and copy of PAN card. Cancelled cheque & PAN card is to be submitted only once]	
3.	Complete Bank Account No. of the Firm [beneficiary]. [in case of change in bank account vendor should write to Account Office]	
4.	Bank Name	
5.	Branch Address	
6.	IFSC Code No.	
7.	Permanent Account Number	
8.	Mobile No. [for SMS]	
9.	Email ID [for information]	

We undertake that all information provided above is correct and MNNIT Allahabad will not be responsible in case of any error on the part of firm.

[Seal and Signature of the firm]